LISHUI E-ABLE POWER EQUIPMENT CO., LTD
No.368, Chengbei Road, Liandu District, 323000, Lishui City, Zhejiang, China
www.e-ablepower.com | arthur@e-ablepower.com | WhatsApp +86 153 5558 9600

E-ABLE POWER / SOLAR GARDEN LIGHT / LAWN

Solar Lawn Light CPD 0705

Little Pumpkin · H500 / H700 mm · 2 W · IP65 · 180°

The Little Pumpkin is a H500 / H700 mm garden light that pushes straight into a planting bed, so it needs no plinth and no supply cable. The head carries a 2 W / 5 V monocrystalline panel and a 3.2 V / 3000 mAh LiFePO4 battery, and switches itself on at dusk; a full charge covers 3–5 overcast days.

The housing is die-cast aluminium with a PC diffuser, sealed to IP65. Light is distributed over 180°, so the fixture reads as a marker along a bed edge rather than as a spotlight: at 2–4 m mounting height it lays a soft pool on the ground and keeps the glow out of windows.

IN THIS DATASHEET

01	Technical data	Page 2
02	Dimensions	Page 3
03	Construction	Page 4
04	Applications	Page 5



IP65	2 W	115–108	3–5	180°	Φ185
PROTECTION	PANEL	LUMEN	RAINY DAYS	BEAM	HEAD, MM

KEY FEATURES

01

Die-cast aluminium body
One-piece casting, corrosion resistant, fixed with stainless fasteners.

Monocrystalline panel
2 W / 5 V panel in the head; charges in overcast weather.

LiFePO4 battery
3.2 V / 3000 mAh; stable chemistry, deep-cycle tolerant.

180° distribution
Light spread over 180° so the pool stays on the walking surface.

Dusk-to-dawn control
Automatic on at dusk, off at dawn; no timer to set.

IP65 protection
Sealed against rain and dust for permanent outdoor use.

ORDERING OPTIONS

Model	Size	Power	Mounting	Head
CPD-0705 / H500	H500 mm	2 W	Ground spike	Φ185 mm
CPD-0705 / H700	H700 mm	2 W	Ground spike	Φ185 mm

E-AblePower Technology

LISHUI E-ABLE POWER EQUIPMENT CO., LTD
No.368, Chengbei Road, Liandu District, 323000, Lishui City, Zhejiang, China
www.e-ablepower.com | arthur@e-ablepower.com | WhatsApp +86 153 5558 9600

TECHNICAL DATA

02

Values are transcribed from the supplier parameter table for CPD-0705. The body is die-cast aluminium, anodised, carrying a ribbed PC shade; the pole is supplied in sections with the 160 mm spike. The battery is rated for more than 2 000 charge cycles.

Item	H500 mm	H700 mm
Electrical		
Rated power	2 W	2 W
Input voltage	DC 3.2 V	DC 3.2 V
Solar panel	2 W / 5 V monocrystalline	2 W / 5 V monocrystalline
Battery	3.2 V / 3000 mAh LiFePO4	3.2 V / 3000 mAh LiFePO4
Charging time	4–6 h by bright sunlight	4–6 h by bright sunlight
Autonomy	3–5 rainy days	3–5 rainy days
Controller	Dusk-to-dawn sensor, PWM controller, waterproof push switch	Dusk-to-dawn sensor, PWM controller, waterproof push switch
Optical		
Light source	2835 SMD LED, 20 pcs	2835 SMD LED, 20 pcs
Luminous flux	115 lm (3000K) / 108 lm (6500K)	115 lm (3000K) / 108 lm (6500K)
Colour temperature	3000K – 6500K	3000K – 6500K
CRI (Ra)	> 80	> 80
Beam angle	180°	180°
Construction		
Material	Die-cast aluminium + PC	Die-cast aluminium + PC
Lamp colour	Black (other colours on request)	Black (other colours on request)
Head size	Φ185 mm	Φ185 mm
Overall size	Φ185 × H500 mm	Φ185 × H700 mm
Net weight	0.79 kg	0.79 kg
Mounting	Ground spike	Ground spike
Operating		
Protection	IP65	IP65
Operating temperature	−25 to +50 °C	−25 to +50 °C
Humidity	10–90 %	10–90 %
Installation height	2–4 m	2–4 m
Warranty	2 years	2 years
Certifications	CE, RoHS, IP65	CE, RoHS, IP65
Packing		
Inner box	1 pc, 200 × 185 × 180 mm	1 pc, 200 × 185 × 180 mm
Outer carton	10 pcs, 940 × 415 × 200 mm	10 pcs, 940 × 415 × 200 mm
Gross weight	10.8 kg (outer, 10 pcs)	10.8 kg (outer, 10 pcs)

NOTES


- Values are transcribed from the supplier specification sheet for this model. Where a range is given, the lower figure applies to the warm-white version and the upper to the cool-white version.
- Autonomy figures assume a full charge, the factory dusk-to-dawn program and normal winter insolation for the latitude of installation.
- Luminous flux and CRI are quoted per colour temperature; the two are measured separately on the production sample.

E-AblePower Technology

LISHUI E-ABLE POWER EQUIPMENT CO., LTD
No.368, Chengbei Road, Liandu District, 323000, Lishui City, Zhejiang, China
www.e-ablepower.com | arthur@e-ablepower.com | WhatsApp +86 153 5558 9600

DIMENSIONS

03



CPD-0705 · H700 body 540 mm plus a 160 mm spike

Overall height is given with the 160 mm spike fitted: a 340 mm body gives H500, a 540 mm body gives H700. The head measures Φ185 mm; the drawing is the supplier artwork.

The luminaire is supplied with a ground spike: it pushes into soil or mulch and needs no plinth, no concrete and no cable. Set the spike to two-thirds of its length so the head stays stable in wind.

INSTALLATION SEQUENCE

- **1 · Set out the line.** Mark centres at 2–4 m along a bed edge, keeping 0.3 m clear of the paving so the head does not overhang the walkway.
- **2 · Drive the spike.** Push the spike into moist soil to two-thirds of its length; on compacted ground, make a pilot hole first rather than hammering the body.
- **3 · Check the head.** Confirm the head is level and the panel faces the noon sun; the sensor window must not be shaded by planting.
- **4 · Commission.** Press the switch and wait 3 s; the lamp lights only in darkness. A full charge takes one clear day.

SUPPLIED BY E-ABLE

- Luminaire head with integrated panel and battery
- Ground spike
- Fixing screws

BY THE PROJECT

- Paving or soil to receive the spike
- Clearance from irrigation lines

LISHUI E-ABLE POWER EQUIPMENT CO., LTD
No.368, Chengbei Road, Liandu District, 323000, Lishui City, Zhejiang, China
www.e-ablepower.com | arthur@e-ablepower.com | WhatsApp +86 153 5558 9600

CONSTRUCTION

04



BUILD AND MATERIALS

Construction	
Light source	2835 SMD LED, 20 pcs, rated 80 000–100 000 h
Diffuser	PC translucent diffuser, even distribution
Body	One-piece die-cast aluminium, corrosion resistant
Solar panel	Monocrystalline 2 W / 5 V, integrated in the head
Battery	LiFePO4 3.2 V / 3000 mAh, more than 2 000 cycles
Control	Dusk-to-dawn sensor, PWM controller, waterproof push switch

The 180° distribution and the ribbed shade spread the beam along the bed edge instead of throwing it forward, so the head does not read as a bright point from the house. Press the switch once and allow 3 s; the lamp then follows the sensor.

WHAT TO SPECIFY

- **Height.** H500 / H700 mm covers border and path-edge use; taller heads clear ground cover and low shrubs.
- **Light colour.** 3000K – 6500K: 3000K for warm residential beds, 6500K where a cooler, brighter edge is wanted.
- **Spacing.** 2–4 m along a bed edge; wider spacing reads as accent points rather than a continuous line.

E-AblePower Technology

LISHUI E-ABLE POWER EQUIPMENT CO., LTD
No.368, Chengbei Road, Liandu District, 323000, Lishui City, Zhejiang, China
www.e-ablepower.com | arthur@e-ablepower.com | WhatsApp +86 153 5558 9600


APPLICATIONS

05

A H500 / H700 mm spike light is a **marker**, not a floodlight: it draws the edge of a bed or the line of a path so people read the route at night. The five settings below are the ones this model is ordered for most often.

WHERE IT FITS

- **Villa gardens and planting beds** — one unit every 2–4 m along the bed edge; the spike needs no plinth, so beds can be replanted without moving the light.
- **Path edges and stepping-stone walks** — keep the head 0.3 m clear of the paving so the light washes the stones instead of shining into the eyes.
- **Community green strips** — repeat in pairs at entrances and at path junctions, where a single unit is not enough to mark the change of direction.
- **Hotel and resort landscaping** — the housing is decorative by day, so units can be placed inside planting rather than along the kerb.
- **Municipal parks and footpaths** — solar units avoid trenching and cable joints; 3–5 overcast days of autonomy covers most temperate sites.











Selection note: 2–4 m spacing for path edges, 4–6 m for accent groups; keep the panel facing the noon sun and clear of ground cover that will grow over it.

Specifications are nominal and may change without notice. The contractual revision is the one confirmed in the order acknowledgement.